## DECOSPAN.

## **DECLARATION OF PERFORMANCE**

## IN ACCORDANCE WITH THE CONSTRUCTION PRODUCTS REGULATION (EU) No. 305/2011

## **DOP 20008**

- 1. Unique identification code of the product-type: Veneered wood-based panels
- 2. Type, batch or serial number or any other element allowing identification of the construction product: Shinnoki, Querkus, Nordus
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

The products are intended for internal use as non-structural component in dry conditions -service class 1

- 4. ACVP class: 3
- 5. Norm reference: EN 13986:2004+A1:2015
- In case of the declaration of performance concerning a construction product covered by a harmonised standard. Determination of formaldehyde emissions according (EN 717-1): Eurofins product testing A/S, Smedeskovvej 38, 8464 Galten Denmark, Test reports 392-2017-00358206, 392-2018-00119401 and 392-2018-00485605
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): Decospan N.V., Lageweg 33, B-8930 Menen, Belgium. Produced at Lageweg 33, B-9830 Menen and Ringlaan 3, B-9830 Menen

Product	Unit	Refer	rence	Shinnoki	Querkus	Nuxe
Core Panel				MDF	MDF	MDF
Thickness veneer	mm			0.6	0.6-2.0	0.6
Min. Mean Density	kg/m³			730	730	730
Total Thickness	mm			19	19-22	19
Veneered				2- sided	2- sided	2- sided
Pre lacquered				2-sides	No	No
Dimensions	mm			2790 x 1240	2500 x 1240 2800 x 2070 3050 x 1220	3050 x 1220 2500 x 1240
Bending strength	N/mm²	EN 310	Length Width	23,0 12,2	23,0 12,2	23,0 12,2
Internal bond	N/mm²	EN 319		0,45 ±0,05	0,45 ±0,05	0,45 ±0,05
Formaldehyde Emission		EN 717-1		E1	E1	E1
Reaction to fire	Class	EN 13986 EN 13501-1		D-s1,d0	D-s2,d0*	D-s2,d0*
Water vapour permeability	Wet Dry	EN 13986 Table 9		NPD	NPD	NPD
Biological durability	Class	EN 335		1	1	1
Content PCP [ppm]	ppm	EN 13986 §5.18		<5	<5	<5

\* Linked with the mean density and the overall thickness and installed with a closed air gap behind the wood-based panel – CWFT EN13986:2004+A1:2015 - table 8

24/02/2025 Pieterian Desmet, CEO -